

GARLOCK KLOZURE® HIGH-PERFORMANCE DYNAMIC SEALS

MILL-RIGHT® N Oil Seals

Highly Abrasion Resistant, Chemically Compatible, Low Wear Seals

When up-time in your plant is critical, trust the new MILL-RIGHT® N elastomer to keep you running! MILL-RIGHT N has been specifically engineered to have the highest abrasion resistance and lowest wear of any Nitrile seal in the industry. This translates to higher equipment efficiencies, longer bearing life, increased production and less maintenance.

For ease of identification, the new MILL-RIGHT N is color coded black.

Proven performance, proven technology, a trusted name...Garlock Klozure®.



MILL-RIGHT® N
(NBR)
BLACK

200°F Continuous
Operating Temp.
250°F Peak Temp.

Benefits

- ▶ Breakthrough abrasion and wear properties for extended service life
- ▶ Improved chemical resistance
- ▶ Low coefficient of friction for less heat generation and lower power consumption
- ▶ Available on all elastomeric Garlock Klozure oil seal designs

Industries Served

- | | |
|------------------------------------|--------------------------|
| ▶ Mining | ▶ Food & Pharmaceutical |
| ▶ Pulp & Paper | ▶ Hydrocarbon Processing |
| ▶ Original Equipment Manufacturers | ▶ General Industry |
| ▶ Primary Metals | ▶ Aggregate |



Garlock Klozure®
HIGH-PERFORMANCE DYNAMIC SEALS


an EnPro Industries company

New MILL-RIGHT® N Materials vs. Conventional Elastomers

Specially engineered elastomers use the latest technology to give the new MILL-RIGHT N elastomer up to a 73% improvement in abrasion resistance over standard materials!



MILL-RIGHT® N



* Bonded seals do not utilize MILL-RIGHT® materials

FOR MORE INFORMATION,
CONTACT YOUR CUSTOMER
SATISFACTION SPECIALIST

1.866.KLOZURE (1.866.556.9873)
FAX 1.866.OILSEAL (1.866.645.7325)

A U T H O R I Z E D D I S T R I B U T O R

WARNING:

Properties/applications shown throughout this brochure are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult Garlock. Failure to select the proper sealing products could result in property damage and/or serious personal injury.

Performance data published in this brochure has been developed from field testing, customer field reports and/or in-house testing.

While the utmost care has been used in compiling this brochure, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Subject to change without notice.

GARLOCK is a registered trademark for packings, seals, gaskets, and other products of Garlock.

© Garlock Inc 2007. All rights reserved worldwide.

MILL-RIGHT® and KLOZURE® are registered trademarks of Garlock Inc.

Garlock Klokzure®

A Division of Garlock Sealing Technologies®

1666 Division Street

Palmyra, New York 14522 USA

1.315.597.4811

Fax 1.315.597.3140

Toll Free 1.866.KLOZURE (1.866.556.9873)

Toll Free Fax: 1.866.OILSEAL (1.866.645.7325)

Visit Klokzure:

www.klokzure.com

Other Garlock brand facilities are located in:

Columbia, SC, USA	1-803-783-1880	Fax: 1-803-783-4279
Houston, TX, USA	1-281-840-4800	Fax: 1-281-840-4756
Sydney, Australia	61-2-9793-2511	Fax: 61-2-9793-2544
São Paulo, Brazil	55-11-4352-6161	Fax: 55-11-4352-8181
Sherbrooke, Canada	1-819-563-8080	Fax: 1-819-563-5620
West Yorkshire, England	44-1422-313600	Fax: 44-1422-313601
Saint-Étienne, France	33-4-7743-5100	Fax: 33-4-7743-5151
Neuss, Germany	49-2131-3490	Fax: 49-2131-349-222
Mexico City, Mexico	52-55-50-78-46-00	Fax: 52555-368-0418
Shanghai, China	86-021-62789702	Fax: 86-021-62787826
Singapore	65-6285-9322	Fax: 65-6284-5843
Dubai, UAE	971-4-8833652	Fax: 971-4-8833682

PRINTED IN U.S.A.

KLZ 2:85

VIA-11/07-REV A

Garlock Klokzure®
HIGH-PERFORMANCE DYNAMIC SEALS

an EnPro Industries company

Bring Garlock Klokzure® to all your sealing requirements

