

Boiler Gaskets & Seals

Non Asbestos Sealing Solutions for Steam



Boiler Gaskets & Seals

Uncured Rubber Gasket Cloth (Tacky Cloth)

Manufactured from a fiberglass yarn that has been twisted with a brass wire for additional strength and density and then coated with an uncured natural rubber. For low pressure gasket requirements. Service temperature of 500° F. This is the base fabric utilized for manufacturing folded gaskets, boiler folded tape and tadpole seals. The gasket cloth is available standard in both brass wire inserted and plain. Material can be laminated to achieve various thicknesses. Also available lightly dusted, graphited, PTFE coated, etc.

Style MM5594-Brass Wire Inserted

Style MM5595-No Wire

Boiler Handhole / Manhole Gaskets

Standard Handhole / Manhole Gaskets are manufactured from **Style MM5594-Brass Wire Inserted** uncured natural rubber coated fabric. (description above) For use in low pressure gasket applications. Excellent for use on uneven flanges. Service temperature to 500°F and maximum 300 psi. The folded gaskets are lightly dusted and are also available with graphite or PTFE surface coating. A variety of standard sizes are available. Custom configurations also available.

Boiler Tadpole Tape

Standard Boiler Tadpole Tape is manufactured from **Style MM5594-Brass Wire Inserted** uncured natural rubber coated fabric as the outer cover and **FRB-Soft** and **FRB-Dense Rope** as the core. For use in low pressure gasket applications. Service temperature to 500°F and maximum 300 psi. Standard bulb diameter from 3/8" - 1" and overall width from 1" - 3". Standard shape utilizes single bulb-single tail. This product is a great gasket material for service against steam, water, air and gases. Other Tadpole Seals available for a variety of other applications. Can also be supplied as a folded boiler tape manufactured from **Style MM5594-Brass Wire Inserted**. A variety of sizes available.

Knitted Fiberglass Rope for Boilers

Manufactured from continuous filament E-Glass yarns, texturized for added volume and knitted into two standard styles. **FRB-Soft** and **FRB-Dense** Knitted Ropes are available from 1/4' - 1 1/2". Other sizes available upon request. Service temperature to 1000°F. Excellent for use in door grooves as well as caulking to seal various crevices. **Style FSB-Dense Fiberglass Square Braid Rope** also available from 1/4" - 3" cross-section.

Custom Boiler Gaskets

McAllister Mills manufactures various types of Custom Boiler Gaskets for most varieties of Industrial and Commercial boilers. These may include; square or rectangular shapes, large diameter endless tadpole gaskets, etc. We welcome the opportunity to view your specific boiler gasket requirements.

McAllister Mills, Inc. 173 Rainbow Circle Independence, VA 24348
800-662-9745 276-773-3114 276-773-2451 Fax