

GARLOCK KLOZURE® HIGH-PERFORMANCE DYNAMIC SEALS

GUARDIAN™ Metallic Bearing Isolator

The Metallic Isolator that can be installed without the use of an arbor press

- ▶ Engineered unitizing element ensures no internal metal-to-metal contact
- ▶ No wear on shaft or metallic components
- ▶ Cam-Lock design means easy installation — No tools required
- ▶ Surpasses IEEE 841-2001 Test Standards
- ▶ Rated to IP56 Per NEMA MG 1-2003
- ▶ API Compliant
- ▶ Available in a broad range of configurations
- ▶ Enhanced vapor blocking capability

Design Parameters

- ▶ Temperature: -30°F (-34°C) to 400°F (204°C)
- ▶ Shaft-to-bore misalignment to ± 0.020 " (0.51mm)
- ▶ Axial motion to ± 0.025 " (0.64mm)
- ▶ Surface speed to 12,000 fpm (61 m/s)
- ▶ Fluoroelastomer o-rings standard



GARLOCK KLOZURE® HIGH-PERFORMANCE DYNAMIC SEALS



Patented Cam-Lock Design

The patented Cam-lock design of the Guardian™ gives it double the retaining power. This design also allows easy installation by hand, without the need for an arbor press. The interference fit of other designs require special tools for installation and may generate bronze shavings that result in bore scoring.

Patented Unitizing Ring

Unlike other isolators that use a simple o-ring, the patented unitizing ring completely eliminates metal-to-metal contact between the rotor and stator. Lack of axial protection can allow the bronze components to contact. Rotation and misalignment cause abrasion and shredding of the internal o-ring, leading to debris and failure.

AUTHORIZED DISTRIBUTOR

WARNING:

Properties/applications shown throughout this brochure are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult Garlock. Failure to select the proper sealing products could result in property damage and/or serious personal injury.

Performance data published in this brochure has been developed from field testing, customer field reports and/or in-house testing.

While the utmost care has been used in compiling this brochure, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Subject to change without notice.

GARLOCK is a registered trademark for packings, seals, gaskets, and other products of Garlock.

© Garlock Inc 2009. All rights reserved worldwide.

Garlock Klozure®

A Division of Garlock Sealing Technologies®

1666 Division Street
Palmyra, New York 14522 USA

1.315.597.4811

Fax 1.315.597.3140

Toll Free 1.866.KLOZURE (1.866.556.9873)

Toll Free Fax: 1.866.OILSEAL (1.866.645.7325)

Visit Klozure:

www.klozure.com

Other Garlock brand facilities are located in:

Columbia, SC, USA	1-803-783-1880	Fax: 1-803-783-4279
Houston, TX, USA	1-281-840-4800	Fax: 1-281-840-4756
Sydney, Australia	61-2-9793-2511	Fax: 61-2-9793-2544
São Paulo, Brazil	55-11-4352-6161	Fax: 55-11-4352-8181
Sherbrooke, Canada	1-819-563-8080	Fax: 1-819-563-5620
West Yorkshire, England	44-1422-313600	Fax: 44-1422-313601
Saint-Étienne, France	33-4-7743-5100	Fax: 33-4-7743-5151
Neuss, Germany	49-2131-3490	Fax: 49-2131-349-222
Mexico City, Mexico	52-55-50-78-46-00	Fax: 52-555-368-0418
Shanghai, China	86-021-62789702	Fax: 86-021-62787826
Singapore	65-6285-9322	Fax: 65-6284-5843
Dubai, UAE	971-4-8833652	Fax: 971-4-8833682
Pune, India	91-20-3061-6608	Fax: 91-20-3061-6699

PRINTED IN U.S.A.

KLZ 2:62

VIA-1/09-Rev C



Garlock Sealing Technologies® is an EnPro Industries company.

Bring Garlock Klozure® to all your sealing requirements

